

TECHNICAL SHEET

PAINTED SURFACES - BARE ALUMINUM - PAINTED METAL - WOOD - GLASS - PLEXIGLASS - PLASTIC





TOUGH ON GRAFFITI AND SOFT ON THE ENVIRONMENT

IMPROVED AND EVEN MORE ECOLOGICAL FORMULA

- Solution C + applies to painted surfaces, bare aluminum, painted metal, wood, glass, plexiglass and plastic
- A biodegradable ecological detergent, without aggressive solvents, to remove spray paint graffiti on smooth surfaces

Prevention

- Wear gloves, protective clothing and boots.
- Wear safety glasses or visor.
- Wear a mask in enclosed areas.
- Wash hands thoroughly after handling.
- Contaminated work clothes should not be leave the workplace.

Consult the safety data sheet of the product.

Specifications

Color: transparent Boiling point: 184°C Rinsing: water

Biodegradable: yes Acid:

Neutraliser: water Appearance: heterogeneous liquid

Chlorinated solvent: no Lifetime: 12 months Freeze/thaw: yes


Hight pressure: not required

Hot water: not required



BEFORE

AFTER CLEANING



DIRECTION OF USE

- 1. Apply **Solution C+** to the graffiti and using a vaporizer.
- 2. Activate with a soft bristle nylon brush.
- 3. Leave on for 1-2 minutes before rinsing or wiping.
- 4. Check the action by cleaning in a spot of the surface.
- 5. Clean or rinse with water. Never let it dry on the surface.
- 6. Repeat the process if necessary.







T 514 585-6137 1 866 810-3928

info@ecograffiti.com

ECOGRAFFITI.COM

